

Declaration of Performance

Nr. D400-02

1. **Product-type identification:** Dry-Pressed Ceramic Tiles, with water absorption $E_b > 10 \%$
2. **Intended use:** For internal walls
3. **Manufacturer:** VitrA Karo Sanayi ve Ticaret A.Ş.
E-5 Karayolu Üzeri Şifa Mah. Hükümet Caddesi No.5
34941 Tuzla İstanbul -TÜRKİYE
4. **Authorised representative:** VitrA UK Limited
Park 34, Collett, Didcot OX11 7WB, United Kingdom
5. **System of assessment and verification of constancy performance:** System 4

6. Declared performance:

Essential characteristics	Performance	UK Designated technical specification
Reaction to fire	A1	BS EN 14411: 2012
Release of dangerous substance, for:		
- Cadmium	NPD / No Performance Determined	BS EN 14411: 2012
- Lead	NPD / No Performance Determined	BS EN 14411: 2012
- Other	NPD / No Performance Determined	BS EN 14411: 2012
Bond strength/adhesion for:		
- Cementitious adhesive, type C	NPD / No Performance Determined	BS EN 14411: 2012
- Dispersion adhesive	NPD / No Performance Determined	BS EN 14411: 2012
- Reaction resin adhesive	NPD / No Performance Determined	BS EN 14411: 2012
- Mortar	NPD / No Performance Determined	BS EN 14411: 2012
Thermal shock resistance	Pass	BS EN 14411: 2012
Durability For:		
-Internal Use	Pass	BS EN 14411: 2012

7. The performance of the product identified in point 1 is in conformity with the declared performances in point 6. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Bayram Bülent Maşa – Quality Assurance Manager
Name and Function

BOZÜYÜK – 01/11/2023
Place and date of issue

Signature

